

LECIP



All-in-one Validator LV-700

Key Features

5.7 inch full-color LCD touch screen
Accepts multiple smart card formats
QR code reader (optional)

WiFi / Bluetooth wireless connection
4G modem (optional)



Technical Specifications

Dimensions	W 5.55" x H 9.72" x D 3.58" (W 141mm x H 247mm x D 91mm)
Contactless Communication	ISO 14443 A/B, ISO 18092 (NFC Forum Reader/Writer mode)
Supported Tag -ICs	MIFARE Classic / Plus / Ultralight / Ultralight C / DESFire/ SmartMX, FeliCa and Calypso
Passenger Display	5.7" LCD 24 LVDS VGA (640x480 Resolution)
Wireless Function	WiFi(802.11b/g/n)/Bluetooth(BLE4.2)
Communication Interface	2x RS232 , 1x RS485,1 x USB micro type B, 4x GPIO (2x In, 2x Out)
Electrical Power	Power Supply 9 to 36V DC Power Consumption 5W - 13W
Other	EMVCo: L1, Operating System : Linux, SIM: Mini 1x, SAM: 4x, MicroSD:1x Ethernet Port: 10/100 Mbps System: 1GHz CPU with GPU, 4G Flash, 1G RAM, Option: QR Code/ Barcode Scanner 4G Modem



Built-in QR code reader (optional) enhances payment choices



Modular design allows easy maintenance-quickly attach and detach

LECIP INC.

881 IL Route 83, Bensenville, IL 60106, USA
+1-312-626-2525 <http://www.lecipinc.com>